

Recessed Square Downlight




Our **ECOLITE** range has a broad appeal and a variety of applications. Commercial, Architectural and Retail sectors alike.

With a functional design and uniform appearance, our D300 series are perfect for commercial environments with conventional ceilings such as offices, hospitals, large areas, retail, restaurants and corridors..

Our D300 series offers superior operating lifespan and low maintenance requirements

Apart from our standard White, Our **SELECT** line provides an extended range of internal components, colours and finishes to suit any environment.

All **ECOLITE** products come standard with a 3-year/50000 hour warranty.



APPLICATIONS

Factory, General Area, Parking Garages

	Standard		SELECT
Luminaire total power (W)	13W	16W	13-16W
Lamp luminous flux*:	2476lm	2940lm	2476 - 2940lm
Luminaire luminous flux*:	1733lm	2058lm	1733 - 2058lm
Luminaire efficacy*:	133lm/W	129lm/W	129 - 133lm/W
Beam Angle:	120°		120°
Rated useful life*	L70 B50 50000 hours		50000 - 100000 hours
Correlated colour temperature*:	3000, 4000 or 5000 Kelvin		2700 - 6500 Kelvin
Colour Rendering Index min:	80		70 - 97
Body Construction:	Mildsteel		Mildsteel
Built-in driver protection:	Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV		Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV
Body Colour:	White		Optional
Dimensions:	195mm X 147mm X 35mm		195mm X 147mm X 35mm
Dimming:	No		Optional
Battery Back-Up:	No		Optional
Serviceable for repairs and maintenance:	Yes		Yes

Due to the rapid improvements taking place in technology, Ultra Light SA reserves the right to adapt or alter any product to improve reliability or performance without prior notice. All values marked with an * are rated values. The nominal flux is based on LED manufacturer's data @ Tsp 85°C. Actual flux output of the luminaire is subject to environmental conditions of the site and the optical efficiency of the luminaire. Luminous flux and electrical load are subject to an initial tolerance of +/- 10%