

Vapour Proof - 2Ft




Our **ECOLITE** range has a broad appeal and a variety of applications. Commercial and Retail sectors alike.

With a functional design and uniform appearance, our V200 series are perfect for car parks, petrol stations, tunnels and warehouses. The Vapour Proof enclosure is IP66 rated and provides flexibility in installation; capable of ceiling and wall mounting and is available in standard 2ft, 4ft, 5ft.

The V201 series vapour proof provides consistent illumination for medium to large areas. Perfect for general illumination in various cover spaces

Suitable for environments subject to moisture and dust, the V200 series offers superior operating lifespan and low maintenance requirements.

All **ECOLITE** products come standard with a 3-year/50000 hour warranty.



APPLICATIONS

Factory, General Area, Parking Garages

	Standard	
	16W	23W
Luminaire total power (W)	16W	23W
Lamp luminous flux*:	2832lm	4145lm
Luminaire luminous flux*:	2549lm	3768lm
Luminaire efficacy*:	159lm/W	163lm/W
Beam Angle:	120°	
Rated useful life*	L70 B50 50000 hours	
Correlated colour temperature*:	4000 or 5000 Kelvin	
Colour Rendering Index min:	80	
Body Construction:	Polycarbonate	
Built-in driver protection:	Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV	
Body Colour:	Grey	
Dimensions:	660mm X 101mm X 101mm	
Dimming:	Optional	
Battery Back-Up:	Optional	
Serviceable for repairs and maintenance:	Yes	

Due to the rapid improvements taking place in technology, Ultra Light SA reserves the right to adapt or alter any product to improve reliability or performance without prior notice. All values marked with an * are rated values. The nominal flux is based on LED manufacturer's data @ Tsp 85°C. Actual flux output of the luminaire is subject to environmental conditions of the site and the optical efficiency of the luminaire. Luminous flux and electrical load are subject to an initial tolerance of +/- 10%

Vapour Proof - 4Ft




Our **ECOLITE** range has a broad appeal and a variety of applications. Commercial and Retail sectors alike.

With a functional design and uniform appearance, our V200 series are perfect for car parks, petrol stations, tunnels and warehouses. The Vapour Proof enclosure is IP66 rated and provides flexibility in installation; capable of ceiling and wall mounting and is available in standard 2ft, 4ft, 5ft.

The V201 series vapour proof provides consistent illumination for medium to large areas. Perfect for general illumination in various cover spaces

Suitable for environments subject to moisture and dust, the V200 series offers superior operating lifespan and low maintenance requirements.

All **ECOLITE** products come standard with a 3-year/50000 hour warranty.



APPLICATIONS

Factory, General Area, Parking Garages

	Standard	
	35W	50W
Luminaire total power (W)	35W	50W
Lamp luminous flux*:	5212lm	6990lm
Luminaire luminous flux*:	4899lm	6570lm
Luminaire efficacy*:	140lm/W	131lm/W
Beam Angle:	120°	
Rated useful life*	L70 B50 50000 hours	
Correlated colour temperature*:	4000 or 5000 Kelvin	
Colour Rendering Index min:	80	
Body Construction:	Polycarbonate	
Built-in driver protection:	Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV	
Body Colour:	Grey	
Dimensions:	1277mm X 101mm X 101mm	
Dimming:	Optional	
Battery Back-Up:	Optional	
Serviceable for repairs and maintenance:	Yes	

Due to the rapid improvements taking place in technology, Ultra Light SA reserves the right to adapt or alter any product to improve reliability or performance without prior notice. All values marked with an * are rated values. The nominal flux is based on LED manufacturer's data @ Tsp 85°C. Actual flux output of the luminaire is subject to environmental conditions of the site and the optical efficiency of the luminaire. Luminous flux and electrical load are subject to an initial tolerance of +/- 10%

Vapour Proof - 5Ft




Our **ECOLITE** range has a broad appeal and a variety of applications. Commercial and Retail sectors alike.

With a functional design and uniform appearance, our V200 series are perfect for car parks, petrol stations, tunnels and warehouses. The Vapour Proof enclosure is IP66 rated and provides flexibility in installation; capable of ceiling and wall mounting and is available in standard 2ft, 4ft, 5ft.

The V201 series vapour proof provides consistent illumination for medium to large areas. Perfect for general illumination in various cover spaces

Suitable for environments subject to moisture and dust, the V200 series offers superior operating lifespan and low maintenance requirements.

All **ECOLITE** products come standard with a 3-year/50000 hour warranty.



APPLICATIONS

Factory, General Area, Parking Garages

	Standard	
Luminaire total power (W)	44W	62W
Lamp luminous flux*:	6750lm	8974lm
Luminaire luminous flux*:	6344lm	8435lm
Luminaire efficacy*:	144lm/W	136lm/W
Beam Angle:	120°	
Rated useful life*	L70 B50 50000 hours	
Correlated colour temperature*:	4000 or 5000 Kelvin	
Colour Rendering Index min:	80	
Body Construction:	Polycarbonate	
Built-in driver protection:	Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV	
Body Colour:	Grey	
Dimensions:	1573mm X 101mm X 101mm	
Dimming:	Optional	
Battery Back-Up:	Optional	
Serviceable for repairs and maintenance:	Yes	

Due to the rapid improvements taking place in technology, Ultra Light SA reserves the right to adapt or alter any product to improve reliability or performance without prior notice. All values marked with an * are rated values. The nominal flux is based on LED manufacturer's data @ Tsp 85°C. Actual flux output of the luminaire is subject to environmental conditions of the site and the optical efficiency of the luminaire. Luminous flux and electrical load are subject to an initial tolerance of +/- 10%