

Up And Down Wall Light (Dual Beam)




Our **ECOLITE** range has a broad appeal and a variety of applications. Commercial, Retail and Architectural sectors alike.

Our **W200 SERIES** wall washers have been designed according to a simple philosophy. Clean lines and geometric shapes are introduced to compliment any existing architectural genre and environment. The result is both minimal and distinct.

Our wall washers have been specifically designed and constructed at the highest levels to produce industry leading performance. Complete aluminium construction provides unrivalled exterior protection against the harshest of climates. Brilliant illuminance ensures less fittings can be used to illuminate the same area.

Apart from our standard Matte Black, Our **SELECT** line provides an extended range of internal components, colours and finishes to suit any environment.

All **ECOLITE** products come standard with a 3-year/50000 hour warranty.



APPLICATIONS

Commercial, Retail, Architectural, Facade, General

	Standard	SELECT
Luminaire total power (W)	4W (2W Up, 2W Down)	4W - 8W
Lamp luminous flux*:	740lm	740 - 1480lm
Luminaire luminous flux*:	518lm	518 - 1036lm
Luminaire efficacy*:	130lm/W	130lm/W
Beam Angle:	120°	15° - 90°
Rated useful life*	L70 B50 50000 hours	50000 - 100000 hours
Correlated colour temperature*:	3000, 4000 or 5000 Kelvin	2700 - 6500 Kelvin
Colour Rendering Index min:	80	70 - 97
Body Construction:	Aluminium	Aluminium
Built-in driver protection:	Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV	Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV
Body Colour:	White or Black	Optional
Dimensions:	104mm X 104mm X 64mm	104mm X 104mm X 64mm
Dimming:	No	No
Serviceable for repairs and maintenance:	Yes	Yes

Due to the rapid improvements taking place in technology, Ultra Light SA reserves the right to adapt or alter any product to improve reliability or performance without prior notice. All values marked with an * are rated values. The nominal flux is based on LED manufacturer's data @ Tsp 85°C. Actual flux output of the luminaire is subject to environmental conditions of the site and the optical efficiency of the luminaire. Luminous flux and electrical load are subject to an initial tolerance of +/- 10%