


Up Or Down Wall Light (Single Beam)




Our **ECOLITE** range has a broad appeal and a variety of applications. Commercial, Retail and Architectural sectors alike.

Our **W300 SERIES** wall washers provide a distinct feature on any wall. The curved cylindrical form creates a bold feature to any space and is designed to stand out rather than blend in. Optional beam angles can provide wide wash or narrow beams depending on your preference.

Our wall washers have been specifically designed and constructed at the highest levels to produce industry leading performance. Complete aluminium construction provides unrivalled exterior protection against the harshest of climates. Brilliant illuminance ensures less fittings can be used to illuminate the same area.

Apart from our standard Matte Black, Our **SELECT** line provides an extended range of internal components, colours and finishes to suit any environment.

All **ECOLITE** products come standard with a 3-year/50000 hour warranty.



APPLICATIONS

Commercial, Retail, Architectural, Facade, General

	Standard		SELECT
Luminaire total power (W)	11W	17W	11 - 17W
Lamp luminous flux*	1816lm	2521lm	1816 - 2521lm
Luminaire luminous flux*	1271lm	1765lm	1271 - 1765lm
Luminaire efficacy*	115lm/W	103lm/W	103 - 115lm/W
Beam Angle:	120°		15° - 90°
Rated useful life*	L70 B50 50000 hours		50000 - 100000 hours
Correlated colour temperature*:	3000, 4000 or 5000 Kelvin		2700 - 6500 Kelvin
Colour Rendering Index min:	90		70 - 97
Body Construction:	Aluminium		Aluminium
Built-in driver protection:	Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV		Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV
Body Colour:	White or Black		Optional
Dimensions:	216mm X 100mm X 132mm		216mm X 100mm X 132mm
Dimming:	No		Optional
Serviceable for repairs and maintenance:	Yes		Yes

Due to the rapid improvements taking place in technology, Ultra Light SA reserves the right to adapt or alter any product to improve reliability or performance without prior notice. All values marked with an * are rated values. The nominal flux is based on LED manufacturer's data @ Tsp 85°C. Actual flux output of the luminaire is subject to environmental conditions of the site and the optical efficiency of the luminaire. Luminous flux and electrical load are subject to an initial tolerance of +/- 10%