

Surface/Suspended Linear - 0.6m External Driver



Our **ECOLITE** range has a broad appeal and a variety of applications. Commercial, Retail and Architectural sectors alike.

Our **L100 SERIES** linears are a great addition to any commercial and retail space. Linears provide seamless illumination perfect for general lighting applications at various lengths. Sleek profiles blend into any existing space providing illumination without distraction.

We have a variety of models within the **L100** range, to suit any aesthetic. The **L100** range can be surface mounted or suspended, as well as integrated and remote driver systems.

The **L104** can be configured with the choice of single colour or Tunable White illumination, coupled with the choice of 7 standard lengths in the range. Variety for all types of applications and spaces.

Apart from our standard Matte Black, Our **SELECT** line provides an extended range of internal components, colours and finishes to suit any environment.

All **ECOLITE** products come standard with a 3-year/50000 hour warranty



APPLICATIONS

Commercial, Retail, Office, General, Architectural

	Standard		SELECT
Luminaire total power (W)	10W	14W	10 - 14W
Lamp luminous flux*:	1725lm	2405lm	1725lm - 2405lm
Luminaire luminous flux*:	1242lm	1732lm	1242lm - 1732lm
Luminaire efficacy*:	131lm/W	128lm/W	128 - 131lm/W
Beam Angle:	120°		120°
Rated useful life*	L70 B50 50000 hours		50000 - 100000 hours
Correlated colour temperature*:	3000, 4000 or 5000 Kelvin		3000 - 6500 Kelvin
Colour Rendering Index min:	80		80 - 90
Body Construction:	Aluminium		Aluminium
Built-in driver protection:	Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV		Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV
Body Colour:	White Or Black		Optional
Dimensions:	564mm X 35mm X 35mm		564mm X 35mm X 35mm
Dimming:	Optional		Optional
Battery Back-Up:	Optional		Optional
Serviceable for repairs and maintenance:	Yes		Yes

Due to the rapid improvements taking place in technology, Ultra Light SA reserves the right to adapt or alter any product to improve reliability or performance without prior notice. All values marked with an * are rated values. The nominal flux is based on LED manufacturer's data @ Tsp 85°C. Actual flux output of the luminaire is subject to environmental conditions of the site and the optical efficiency of the luminaire. Luminous flux and electrical load are subject to an initial tolerance of +/- 10%

Surface/Suspended Linear - 0.8m External Driver



Our **ECOLITE** range has a broad appeal and a variety of applications. Commercial, Retail and Architectural sectors alike.

Our **L100 SERIES** linears are a great addition to any commercial and retail space. Linears provide seamless illumination perfect for general lighting applications at various lengths. Sleek profiles blend into any existing space providing illumination without distraction.

We have a variety of models within the **L100** range, to suit any aesthetic. The **L100** range can be surface mounted or suspended, as well as integrated and remote driver systems.

The **L104** can be configured with the choice of single colour or Tunable White illumination, coupled with the choice of 7 standard lengths in the range. Variety for all types of applications and spaces.

Apart from our standard Matte Black, Our **SELECT** line provides an extended range of internal components, colours and finishes to suit any environment.

All **ECOLITE** products come standard with a 3-year/50000 hour warranty



APPLICATIONS

Commercial, Retail, Office, General, Architectural

	Standard		SELECT
Luminaire total power (W)	14W	20W	14 - 20W
Lamp luminous flux*:	2590lm	3610lm	2590lm - 3610lm
Luminaire luminous flux*:	1865lm	2599lm	1865lm - 2599lm
Luminaire efficacy*:	131lm/W	128lm/W	128 - 131lm/W
Beam Angle:	120°		120°
Rated useful life*	L70 B50 50000 hours		50000 - 100000 hours
Correlated colour temperature*:	3000, 4000 or 5000 Kelvin		3000 - 6500 Kelvin
Colour Rendering Index min:	80		80 - 90
Body Construction:	Aluminium		Aluminium
Built-in driver protection:	Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV		Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV
Body Colour:	White Or Black		Optional
Dimensions:	844mm X 35mm X 35mm		844mm X 35mm X 35mm
Dimming:	Optional		Optional
Battery Back-Up:	Optional		Optional
Serviceable for repairs and maintenance:	Yes		Yes

Due to the rapid improvements taking place in technology, Ultra Light SA reserves the right to adapt or alter any product to improve reliability or performance without prior notice. All values marked with an * are rated values. The nominal flux is based on LED manufacturer's data @ Tsp 85°C. Actual flux output of the luminaire is subject to environmental conditions of the site and the optical efficiency of the luminaire. Luminous flux and electrical load are subject to an initial tolerance of +/- 10%

Surface/Suspended Linear - 1.1m External Driver



Our **ECOLITE** range has a broad appeal and a variety of applications. Commercial, Retail and Architectural sectors alike.


Our **L100 SERIES** linears are a great addition to any commercial and retail space. Linears provide seamless illumination perfect for general lighting applications at various lengths. Sleek profiles blend into any existing space providing illumination without distraction.

We have a variety of models within the **L100** range, to suit any aesthetic. The **L100** range can be surface mounted or suspended, as well as integrated and remote driver systems.

The **L104** can be configured with the choice of single colour or Tunable White illumination, coupled with the choice of 7 standard lengths in the range. Variety for all types of applications and spaces.

Apart from our standard Matte Black, Our **SELECT** line provides an extended range of internal components, colours and finishes to suit any environment.

All **ECOLITE** products come standard with a 3-year/50000 hour warranty



APPLICATIONS

Commercial, Retail, Office, General, Architectural

	Standard		SELECT
Luminaire total power (W)	19W	27W	19 - 27W
Lamp luminous flux*:	3450lm	4810lm	3450lm - 4810lm
Luminaire luminous flux*:	2484lm	3463lm	2484lm - 3463lm
Luminaire efficacy*:	131lm/W	128lm/W	128 - 131lm/W
Beam Angle:	120°		120°
Rated useful life*	L70 B50 50000 hours		50000 - 100000 hours
Correlated colour temperature*:	3000, 4000 or 5000 Kelvin		3000 - 6500 Kelvin
Colour Rendering Index min:	80		80 - 90
Body Construction:	Aluminium		Aluminium
Built-in driver protection:	Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV		Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV
Body Colour:	White Or Black		Optional
Dimensions:	1124mm X 35mm X 35mm		1124mm X 35mm X 35mm
Dimming:	Optional		Optional
Battery Back-Up:	Optional		Optional
Serviceable for repairs and maintenance:	Yes		Yes

Due to the rapid improvements taking place in technology, Ultra Light SA reserves the right to adapt or alter any product to improve reliability or performance without prior notice. All values marked with an * are rated values. The nominal flux is based on LED manufacturer's data @ Tsp 85°C. Actual flux output of the luminaire is subject to environmental conditions of the site and the optical efficiency of the luminaire. Luminous flux and electrical load are subject to an initial tolerance of +/- 10%

Surface/Suspended Linear - 1.4m External Driver



Our **ECOLITE** range has a broad appeal and a variety of applications. Commercial, Retail and Architectural sectors alike.

Our **L100 SERIES** linears are a great addition to any commercial and retail space. Linears provide seamless illumination perfect for general lighting applications at various lengths. Sleek profiles blend into any existing space providing illumination without distraction.

We have a variety of models within the **L100** range, to suit any aesthetic. The **L100** range can be surface mounted or suspended, as well as integrated and remote driver systems.

The **L104** can be configured with the choice of single colour or Tunable White illumination, coupled with the choice of 7 standard lengths in the range. Variety for all types of applications and spaces.

Apart from our standard Matte Black, Our **SELECT** line provides an extended range of internal components, colours and finishes to suit any environment.

All **ECOLITE** products come standard with a 3-year/50000 hour warranty



APPLICATIONS

Commercial, Retail, Office, General, Architectural

	Standard		SELECT
Luminaire total power (W)	24W	34W	24 - 34W
Lamp luminous flux*:	4315lm	6015lm	4315lm - 6015lm
Luminaire luminous flux*:	3107lm	4331lm	3107lm - 4331lm
Luminaire efficacy*:	131lm/W	128lm/W	128 - 131lm/W
Beam Angle:	120°		120°
Rated useful life*	L70 B50 50000 hours		50000 - 100000 hours
Correlated colour temperature*:	3000, 4000 or 5000 Kelvin		3000 - 6500 Kelvin
Colour Rendering Index min:	80		80 - 90
Body Construction:	Aluminium		Aluminium
Built-in driver protection:	Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV		Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV
Body Colour:	White Or Black		Optional
Dimensions:	1404mm X 35mm X 35mm		1404mm X 35mm X 35mm
Dimming:	Optional		Optional
Battery Back-Up:	Optional		Optional
Serviceable for repairs and maintenance:	Yes		Yes

Due to the rapid improvements taking place in technology, Ultra Light SA reserves the right to adapt or alter any product to improve reliability or performance without prior notice. All values marked with an * are rated values. The nominal flux is based on LED manufacturer's data @ Tsp 85°C. Actual flux output of the luminaire is subject to environmental conditions of the site and the optical efficiency of the luminaire. Luminous flux and electrical load are subject to an initial tolerance of +/- 10%

Surface/Suspended Linear - 1.7m External Driver



Our **ECOLITE** range has a broad appeal and a variety of applications. Commercial, Retail and Architectural sectors alike.

Our **L100 SERIES** linears are a great addition to any commercial and retail space. Linears provide seamless illumination perfect for general lighting applications at various lengths. Sleek profiles blend into any existing space providing illumination without distraction.

We have a variety of models within the **L100** range, to suit any aesthetic. The **L100** range can be surface mounted or suspended, as well as integrated and remote driver systems.

The **L104** can be configured with the choice of single colour or Tunable White illumination, coupled with the choice of 7 standard lengths in the range. Variety for all types of applications and spaces.

Apart from our standard Matte Black, Our **SELECT** line provides an extended range of internal components, colours and finishes to suit any environment.

All **ECOLITE** products come standard with a 3-year/50000 hour warranty



APPLICATIONS

Commercial, Retail, Office, General, Architectural

	Standard		SELECT
Luminaire total power (W)	29W	41W	29 - 41W
Lamp luminous flux*:	5175lm	7215lm	5175lm - 7215lm
Luminaire luminous flux*:	3726lm	5195lm	3726lm - 5195lm
Luminaire efficacy*:	131lm/W	128lm/W	128 - 131lm/W
Beam Angle:	120°		120°
Rated useful life*	L70 B50 50000 hours		50000 - 100000 hours
Correlated colour temperature*:	3000, 4000 or 5000 Kelvin		3000 - 6500 Kelvin
Colour Rendering Index min:	80		80 - 90
Body Construction:	Aluminium		Aluminium
Built-in driver protection:	Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV		Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV
Body Colour:	White Or Black		Optional
Dimensions:	1684mm X 35mm X 35mm		1684mm X 35mm X 35mm
Dimming:	Optional		Optional
Battery Back-Up:	Optional		Optional
Serviceable for repairs and maintenance:	Yes		Yes

Due to the rapid improvements taking place in technology, Ultra Light SA reserves the right to adapt or alter any product to improve reliability or performance without prior notice. All values marked with an * are rated values. The nominal flux is based on LED manufacturer's data @ Tsp 85°C. Actual flux output of the luminaire is subject to environmental conditions of the site and the optical efficiency of the luminaire. Luminous flux and electrical load are subject to an initial tolerance of +/- 10%

Surface/Suspended Linear - 2m External Driver



Our **ECOLITE** range has a broad appeal and a variety of applications. Commercial, Retail and Architectural sectors alike.


Our **L100 SERIES** linears are a great addition to any commercial and retail space. Linears provide seamless illumination perfect for general lighting applications at various lengths. Sleek profiles blend into any existing space providing illumination without distraction.

We have a variety of models within the **L100** range, to suit any aesthetic. The **L100** range can be surface mounted or suspended, as well as integrated and remote driver systems.

The **L104** can be configured with the choice of single colour or Tunable White illumination, coupled with the choice of 7 standard lengths in the range. Variety for all types of applications and spaces.

Apart from our standard Matte Black, Our **SELECT** line provides an extended range of internal components, colours and finishes to suit any environment.

All **ECOLITE** products come standard with a 3-year/50000 hour warranty



APPLICATIONS

Commercial, Retail, Office, General, Architectural

	Standard		SELECT
Luminaire total power (W)	33W	47W	33 - 47W
Lamp luminous flux*:	6040lm	8420lm	6040lm - 8420lm
Luminaire luminous flux*:	4530lm	6315lm	4530lm - 6315lm
Luminaire efficacy*:	136lm/W	134lm/W	134 - 136lm/W
Beam Angle:	120°		120°
Rated useful life*	L70 B50 50000 hours		50000 - 100000 hours
Correlated colour temperature*:	3000, 4000 or 5000 Kelvin		3000 - 6500 Kelvin
Colour Rendering Index min:	80		80 - 90
Body Construction:	Aluminium		Aluminium
Built-in driver protection:	Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV		Voltage fluctuation, overheating, short circuit, overloads, voltage spikes up to 2kV
Body Colour:	White Or Black		Optional
Dimensions:	1964mm X 35mm X 35mm		1964mm X 35mm X 35mm
Dimming:	Optional		Optional
Battery Back-Up:	Optional		Optional
Serviceable for repairs and maintenance:	Yes		Yes

Due to the rapid improvements taking place in technology, Ultra Light SA reserves the right to adapt or alter any product to improve reliability or performance without prior notice. All values marked with an * are rated values. The nominal flux is based on LED manufacturer's data @ Tsp 85°C. Actual flux output of the luminaire is subject to environmental conditions of the site and the optical efficiency of the luminaire. Luminous flux and electrical load are subject to an initial tolerance of +/- 10%